

STOWE



STOWE 220-1202

pantheontile.com | 877.737.3742





STOWE 220-1201

pantheontile.com | 877.737.3742


pantheon[®]
what a difference you'll make

STOWE

OVERVIEW



COLOR OPTIONS

220-1201



220-1202



FORMAT (NOMINAL INCHES) ± 8 mm

12"x24" Non-Rectified Matte


24"x48" Rectified Matte

TRIM LEAD TIMES VARY

3"x24" Bullnose Matte



12"x12" Square Mosaic (2"x2")
Matte



BODY TYPE

Glazed Porcelain

APPLICATIONS

Interior Wall • Floor

TECHNICAL DETAILS

DCOF	≥ 0.42	Passes	ANSI 137.1
Dimensional Tolerance	<0.10%	Compliant	ISO 10545-2
Thickness Tolerance	<5%	Compliant	ISO 10545-2
Water Absorption Porcelain	<0.5%	Passes	ISO 10545-3
Breaking Strength >7.5mm	1300N	Meet / Exceeds	ISO 10545-4
Modulus of Rupture	35N/mm ²	Meet / Exceeds	ISO 10545-4
Deep Surface Abrasion	< 175mm ³	Meet / Exceeds	ISO 10545-6
Frost Resistance	Resists	Resists	ISO 10545-12
Chemical Resistance	Resists	Resists	ISO 10545-13
Stain Resistance	Resists	Resists	ISO 10545-14
V Rating		V2	
Pre-Consumer Recycled Content		20%	
VOC Content		0%	



= #gtg material that is in stock and available in the U.S.
pantheontile.com | 877.737.3742

pantheon®
what a difference you'll make

STOWE



220-1202



12" x 24" Non-Rectified
30 x 60



Matte
8 mm